

ORDER KEY VALVES

1. SERIES

P – Series

2. VERSION

H – normally closed

F – normally open

M – modulating

3. MATERIAL

A – Aluminum

S – Steel

C – Cast Iron

4. NOMINAL DIAMETER (DN)

15, 20, 25, 32, 40, 50, 65, 80, 100, 150, 200, 250, 300

NOTE:

DN 15 to DN 20 Threaded

DN 25 to DN 50 Threaded or Flange, Please indicate **F** for flange (i.e. 25F)

DN 65 to DN 300 Flange

5. VOLTAGE

A – 230 VAC

D – 24 VDC

6. TYPE

H – single stage

B – dual stage

C – liquid

M – with electric power drive

T – 1 Stage slow opening mode

7. PRESSURE RANGE

02 – 200 mBar

05 – 500 mBar

1 – 1 Bar

2 – 2 Bar

3 – 3 Bar

4 – 4 Bar

6 – 6 Bar

8. ACCESSORIES

X – without any accessories

K – with gas flow adjustment

P – position indicator

E – EX proof

EXAMPLES FOR
ORDER KEY VALVES

P	H	A	2	5	A	H	1	K
---	---	---	---	---	---	---	---	---

P	H	A	2	5	F	A	H	1	K
---	---	---	---	---	---	---	---	---	---